

## References

- Agarwala, V., & Dixit, D. (1981). Fabrication of Aluminium Base Composite by Foundry Technique. *Transaction of Japan Institute of Metals*, 22(8), 521-526. doi:<https://doi.org/10.2320/matertrans1960.22.521>
- Ahlatci, H., Kocer, T., Candan, E., & Cimenog lu, H. (2006). Wear behaviour of Al=(Al<sub>2</sub>O<sub>3</sub>pCSiCp) hybrid composites. *Tribology International*, 39, 213-220. doi:[10.1016/J.TRIPOINT.2005.01.029](https://doi.org/10.1016/J.TRIPOINT.2005.01.029)
- Ahmad, S. N., Hashim, J., & Ghazali, M. I. (2007). Effect of porosity on tensile properties of cast particle reinforced MMC. *Journal of Composite Materials*, 41(5), 575-589. doi:<https://doi.org/10.1177/0021998306066720>
- Ahn, B. W., Choi, D. H., Kim, Y. H., & Jung, S. B. (2012). Fabrication of SiCp/AA5083 composite via friction stir welding. *Transaction Nonferrous Metal Society of China*, 22, 634-638. doi:[https://doi.org/10.1016/S1003-6326\(12\)61777-4](https://doi.org/10.1016/S1003-6326(12)61777-4)
- Aleksendric, D., & Carbone, P. (2015). *Soft Computing in the Design and Manufacturing of Composite Materials: Applications to Brake Friction and Thermoset Matrix Composites*. Cambridge: Woodhead Publishing. doi:<https://doi.org/10.1016/C2014-0-03652-0>
- Amirizad, M., Kokabi, A. H., Gharacheh, M. A., Sarrafi, R., Shalchi, B., & Azizieh, M. (2006). Evaluation of microstructure and mechanical properties in friction stir welded A356+15%.SiCp cast composite. *Materials Letters*, 60, 565-568. doi:<https://doi.org/10.1016/j.matlet.2005.09.035>
- Amouri, K., Kazemi, S., Momeni, A., & Kazazi, M. (2016). Microstructure and mechanical properties of Alnano/micro SiC composites produced by stir casting technique. *Materials Science & Engineering A*, 674, 569-578. doi:<https://doi.org/10.1016/j.msea.2016.08.027>
- Aqida, S. N., Ghazali, M. I., & Hashim, J. (2012). Effects of Porosity on Mechanical Properties of Metal Matrix Composite: An Overview. *Jurnal Teknologi*, 40((A)), 17-32. doi:[10.11113/jt.v40.395](https://doi.org/10.11113/jt.v40.395)
- Archard, J. F. (1953). Contact and Rubbing of Flat Surfaces. *Journal of Applied Physics*, 24, 981-988. doi:<https://doi.org/10.1063/1.1721448>
- Archard, J., & W., H. (1956). The wear of metals under unlubricated conditions. *Proceedings of the Royal Society of London. Series A. Mathematical and Physical Sciences*, 236,

397-410. doi:<https://doi.org/10.1098/rspa.1956.0144>

Astarita, A., Squillace, A., & Carrino, L. (2014). Experimental study of the forces acting on the tool in the friction stir welding of AA 2024-T3 sheets. *Journal of Material Engineering and Performance*, 3754-3761. doi:<https://doi.org/10.1007/s11665-014-1140-3>

Azizieh, M., Kokabi, A. H., & Abachi, P. (2011). Effect of rotational speed and probe profile on microstructure and hardness of AZ31/Al<sub>2</sub>O<sub>3</sub> nanocomposites fabricated by friction stir processing. *Material and Design*, 32, 2034-2041. doi:<https://doi.org/10.1016/j.matdes.2010.11.055>

Babu, N. K., Kallip, K., Leparoux, M., Aliogab, A. K., Reddy, G. M., & Talari, M. K. (2016). Characterization of microstructure and mechanical properties of friction stir welded AlMg5-Al<sub>2</sub>O<sub>3</sub> nanocomposites. *Materials Science and Engineering: A*, 658, 109-122. doi:[10.1016/j.msea.2016.01.102](https://doi.org/10.1016/j.msea.2016.01.102)

Bahrami, M., Dehghani, K., & Givi, M. K. (2014). A novel approach to develop aluminum matrix nano-composite employing friction stir welding technique. *Materials and Design*, 53, 217-225. doi:<https://doi.org/10.1016/j.matdes.2013.07.006>

Bahrami, M., Givi, M. K., Dehghani, K., & Parvin, N. (2014). On the role of pin geometry in microstructure and mechanical properties of AA7075/SiC nano-composite fabricated by friction stir welding technique. *Materials and Design*, 53, 519-527. doi:<https://doi.org/10.1016/j.matdes.2013.07.049>

Bahrami, M., Nikoo, M. F., & Givi, M. K. (2014). Microstructural and mechanical behaviors of nano-sized SiC-included AA7075-O FSW joints prepared through two passes. *Materials Science and Engineering A*, 626, 220-228. doi:[10.1016/j.msea.2014.12.009](https://doi.org/10.1016/j.msea.2014.12.009)

Baradeswaran, A., Elayaperumal, A., & Issac, F. R. (2013). A Statistical Analysis of Optimization of Wear Behaviour of Al- Al<sub>2</sub>O<sub>3</sub> Composites Using Taguchi Technique. *Procedia Engineering*, 64, 973-982. doi:[10.1016/j.proeng.2013.09.174](https://doi.org/10.1016/j.proeng.2013.09.174)

Barati, M., Abbasi, M., & Abedini, M. (2019). The effects of friction stir processing and friction stir vibration processing on mechanical, wear and corrosion characteristics of Al6061/SiO<sub>2</sub> surface composite. *Journal of Manufacturing Processes*, 45, 491-497. doi:[10.1016/J.JMAPRO.2019.07.034](https://doi.org/10.1016/J.JMAPRO.2019.07.034)

Bassani, P., Capello, E., Colombo, D., Previtali, B., & Vedani, M. (2007). Effect of process parameters on bead properties of A359/SiC MMCs welded by laser. *Composites: Part A Applied Science and Manufacturing*, 38(4), 1089-1098. doi:<https://doi.org/10.1016/j.compositesa.2006.04.014>

- Behera, R., Datta, A., Chatterjee, D., & Sutradhar, G. (2011). Role of SiCp on the solidification rate and forgeability of stir cast LM6/SiCp MMCs. *International Journal of Scientific and Engineering Research*, 2(1), 1-9. doi:ISSN 2229-5518
- Behnagh, R. A., Givi, M. K., & Akbari, M. (2012). Mechanical properties, corrosion resistance, and microstructural changes during friction stir processing of 5083 aluminium rolled plates. *Material and Manufacturing Processes*, 27(6), 636-640. doi:<https://doi.org/10.1080/10426914.2011.593243>
- Bhadouria, N., Thakur, L., Kumar, P., & Arora, N. (2017). An investigation of normal and submerged condition on microstructural and tribological properties of friction stir processes AZ91-D magnesium alloy. *The Canadian Journal of Metallurgy and Materials Science*, 56(1), 94-103. doi:<https://doi.org/10.1080/00084433.2016.1270394>
- Bharath, V., Ajawan, S. S., Nagaral, M., Auradi, V., & Kori, S. A. (2018). Characterization and Mechanical Properties of 2014 Aluminum Alloy Reinforced with Al<sub>2</sub>O<sub>3</sub>p Composite Produced by Two-Stage Stir Casting Route. *Journal of The Institution of Engineers (India): Series C*, 100(2), 277-282. doi:<https://doi.org/10.1007/s40032-018-0442-x>
- Bharti, S., Ghetiya, N. D., & Patel, K. M. (2020). A review on manufacturing the surface composites by friction stir processing. *Materials and Manufacturing Processes*, 36(2). doi:DOI: 10.1080/10426914.2020.1813897.
- Bharti, S., Ghetiya, N. D., & Patel, K. M. (2020). Micro-hardness and wear behavior of AA2014/Al<sub>2</sub>O<sub>3</sub> surface composite produced by friction stir processing. *SN Applied Sciences*, 2(11), 1760. doi:<https://doi.org/10.1007/s42452-020-03585-2>
- Bowden, F. P., & Tabor, D. (1951). *The Friction and Lubrication of Solids*. New York: Oxford University Press. doi:<https://doi.org/10.1119/1.1933017>
- Bozkurt, Y., Kentli, A., Uzun, H., & Salman, S. (2012). Experimental investigation and prediction of mechanical properties of friction stir welded aluminium metal matrix composite plates. *Journal of Material Science*, 18(4), 336-340. doi:[10.5755/j01.ms.18.4.3092](https://doi.org/10.5755/j01.ms.18.4.3092)
- Bozkurt, Y., Uzun, H., & Salman, S. (2011). Microstructure and mechanical properties of friction stir welded particulate reinforced AA2124/SiC/25p-T4 composite. *Journal of Composite Materials*, 45, 2237-2245. doi:<https://doi.org/10.1177/0021998311401067>
- Cavaliere, P., Cerri, E., Marzoli, L., & Dos Santos, J. (2004). Friction stir welding of ceramic particle reinforced aluminium based metal matrix composites. *Applied Composite*

*Material*, 11, 247-258. doi:10.1023/B:ACMA.0000035478.71092.ec

Ceschini, L., Boromei, I., Minak, G., Morri, A., & Tarterini, F. (2007a). Effect of friction stir welding on microstructure, tensile and fatigue properties of the AA7005/10 vol.%Al<sub>2</sub>O<sub>3</sub>p composite. *Composites Science and Technology*, 67, 605-615. doi:<https://doi.org/10.1016/j.compscitech.2006.07.029>

Ceschini, L., Boromei, I., Minak, G., Morri, A., & Tarterini, F. (2007b). Microstructure, tensile and fatigue properties of AA6061/20 vol.%. Al<sub>2</sub>O<sub>3</sub>p friction stir welded joints. *Composite Part A: Applied Science and Manufacturing*, 38(4), 1200-1210. doi:<https://doi.org/10.1016/j.compositesa.2006.06.009>

Chandrakanth, R. G., Rajkumar, K., & Aravindan, S. (2010). Fabrication of Copper-TiC-Graphite Hybrid Metal Matrix Composites through Microwave Processing. *International Journal of Advanced Manufacturing Technology*, 48(5-8), 645-653. doi:<https://doi.org/10.1007/s00170-009-2474-0>

Chawla, N., & Chawla, K. K. (2006). *Metal Matrix Composites*. Verlag New York: Springer. doi:<https://doi.org/10.1007/978-1-4614-9548-2>

Chen, X. G., Silva, M., Gougeon, P., & St-Georges, L. (2009). Microstructure and mechanical properties of friction stir welded AA6063 - B4C metal matrix composites. *Materials Science and Engineering A*, 518, 174-184. doi:<https://doi.org/10.1016/j.msea.2009.04.052>

Cioffi, F., Fernndez, R., Gesto, D., Rey, P., Verdera, D., & Gonzlez-Doncel, G. (2013). Friction stir welding of thick plates of aluminum alloy matrix composite with a high volume fraction of ceramic reinforcement. *Composites Part A: Applied Science and Manufacturing*, 54, 117-123. doi:<https://doi.org/10.1016/j.compositesa.2013.07.011>

Cook, G. O., & Sorensen, C. D. (2011). Overview of transient liquid phase and partial liquid phase bonding. *Journal of Material Science*, 46(16), 5304-5323. doi:<https://doi.org/10.1007/s10853-011-5561-1>

Dadashpour, M., Mostafapour, A., Yeşildal, R., & Rouhi, S. (2016). Effect of process parameter on mechanical properties and fracture behavior of AZ91C/SiO<sub>2</sub> composite fabricated by FSP. *Material Science and Engineering A*, 655, 379-387. doi:10.1016/j.msea.2015.12.103

Das, S., Udhayabhanu, V., Das, S., & Das, K. (2006). Synthesis and characterization of zircon sand/Al-4.5 wt% Cu composite produced by stir casting route. *Journal of Materials Science*, 41(14), 4668-4677. doi:10.1007/s10853-006-0056-1

Devanathan, C., & Babu, A. S. (2014). Friction Stir Welding of Metal Matrix Composite

- using coated tool. *Procedia Materials Science*, 6, 1470-1475. doi:<https://doi.org/10.1016/j.mspro.2014.07.126>
- Dieter G., E. (1988). *Mechanical metallurgy*. U. K.: Mc Graw-Hill. doi:<https://doi.org/10.1002/crat.2170230211>
- Dinaharan, I. (2016). Influence of ceramic particulate type on microstructure and tensile strength of aluminum matrix composites produced using friction stir processing. *Journal of Asian Ceramic Societies*, 4(2), 209-218. doi:<https://doi.org/10.1016/j.jascer.2016.04.002>
- Dinaharan, I., & Murugan, N. (2012). Effect of friction stir welding on microstructure, mechanical and wear properties of AA6061/ZrB<sub>2</sub> in situ composites. *Materials Science and Engineering A*, 543, 257-266. doi:<https://doi.org/10.1016/j.msea.2012.02.085>
- Dinaharan, I., & Murugan, N. (2012(a)). Optimization of friction stir welding process to maximize tensile strength of AA6061/ZrB<sub>2</sub> in-situ composite butt joints. *Metals and Material International*, 18(1), 135-142. doi:<https://doi.org/10.1007/s12540-012-0016-z>
- Dinaharan, I., Nelsonb, R., Vijay, S. J., & Akinlabi, E. T. (2016). Microstructure and wear characterization of aluminum matrix composites reinforced with industrial waste fly ash particulates synthesized by friction stir processing. *Materials Characterization*, 118, 149-158. doi:<https://doi.org/10.1016/j.matchar.2016.05.017>
- Dinaharan, I., Saravanakumar, S., Kalaiselvan, K., & Gopalakrishnan, S. (2017). Microstructure and sliding wear characterization of Cu/TiB<sub>2</sub> coppermatrix composites fabricated via friction stir processing. *Journal of Asian Ceramic Societies*, 5(3), 295-303. doi:<https://doi.org/10.1016/j.jascer.2017.06.002>
- Dragatogiannis, D. A., Koumoulos, E. P., Kartsonakis, I. A., Pantelis, D. I., & Charitidis, C. A. (2016). Dissimilar Friction Stir Welding Between 5083 and 6082 Al Alloys Reinforced With TiC Nanoparticles. *Materials and Manufacturing Processes*, 31(16), 2010-2114. doi:<https://doi.org/10.1080/10426914.2015.1103856>
- Du, Z. T. (2016). Fabrication of a new Al-Al<sub>2</sub>O<sub>3</sub>-CNTs composite using friction stir processing (FSP). *Material Science and Engineering A*, 667, 125-131. doi:[10.1016/j.msea.2016.04.094](https://doi.org/10.1016/j.msea.2016.04.094)
- Dwivedi, D. K. (2003). Sliding temperature and wear behaviour of cast Al-Si-Mg alloys. *Materials Science and Technology*, 19(8), 1091-1096. doi:<https://doi.org/10.1016/j.msea.2004.05.014>

- Dwivedi, S. P., Sharma, S., & Mishra, R. K. (2014). Microstructure and Mechanical Properties of A356/SiC Composites Fabricated by Electromagnetic Stir Casting. *Procedia Materials Science*, 6, 1524-1532. doi:<https://doi.org/10.1016/j.mspro.2014.07.133>
- Ezatpour, H. R., Sajjadi, S. A., Sabzevar, M. H., & Huang, Y. (2014). Investigation of Microstructure and Mechanical Properties of Al6061-Nanocomposite Fabricated by Stir Casting. *Materials and Design*, 55, 921-928. doi:<https://doi.org/10.1016/j.matdes.2013.10.060>
- Feng, A. H., Xiao, B. L., & Ma, Z. Y. (2008). Effect of microstrucutral evolution on mechanical properties of friction stir welded AA2009/SiCp composite. *Composites Science and Technology*, 68, 2141-2141. doi:<https://doi.org/10.1016/j.compscitech.2008.03.010>
- Fernandez, G. J., & Murr, L. E. (2004). Characterization of tool wear and weld optimization in the friction-stir welding of cast aluminum 359+20% SiC metal-matrix composite. *Materials Characterization*, 52, 65-75. doi:<https://doi.org/10.1016/j.matchar.2004.03.004>
- Galarraga, H., Lados, D. A., Dehoff, R. R., Kirka, M. M., & Nandwana, P. (2016). Effects of the microstructure and porosity on properties of Ti-6Al-4V ELI alloy fabricated by electron beam melting (EBM). *Additive Manufacturing*, 10, 47-57. doi:<https://doi.org/10.1016/j.addma.2016.02.003>
- Garcia, R., Lopez, V. H., Bedolla, E., & Manzano, A. (2003). A comparative study of the MIG welding of Al/TiC composites using direct and indirect electric arc processes. *Journal of Material Science*, 38(12), 2771-2779. doi:[10.1023/A:1024471610718](https://doi.org/10.1023/A:1024471610718)
- Gay, D. (2014). *Composite Materials: Design and Applications*. Boca Raton: CRC Press. doi:ISBN 9780367372897
- Ghosh, P., Ray, S., & Rohatgi, P. (1984). Incorporation of Alumina Particles in Aluminium-Magnesium Alloy by Stirring in Melt. *Transaction of Japan Institute of Metals*, 25(6), 440-444. doi:<https://doi.org/10.2320/matertrans1960.25.440>
- Goni, J., Egizabal, P., Coletto, P., Mitxelena, I., Leunda, I., & Guridi, J. R. (2003). High performance automotive and railway components made from novel competitive aluminium composites. *Journal of Material Science and Technology*, 19, 930-934. doi:<https://doi.org/10.1179/026708303225004413>
- Gopalakrishnan, S., & Murugan, N. (2011). Prediction of tensile strength of friction stir welded aluminium matrix TiCp particulate reinforced composite. *Material and*

*Design*, 32, 462-467. doi:<https://doi.org/10.1016/j.matdes.2010.05.055>

- Gui, M. C., Han, J. M., & Li, P. Y. (2004). Microstructure and mechanical properties of Mg-Al9Zn/SiCp composite produced by vacuum stir casting process. *Materials Science and Technology*, 20(6), 765-771.
- Hashim, J., Looney, L., & Hashmi, M. S. (1999). Metal matrix composites: production by stir casting method. *Journal of Materials Processing Technology*, 92-93, 1-7. doi:[https://doi.org/10.1016/S0924-0136\(99\)00118-1](https://doi.org/10.1016/S0924-0136(99)00118-1)
- Hashim, J., Looney, L., & Hashmi, M. S. (2001). The enhancement of wettability of SiC particles in cast aluminum matrix composite. *Journal of Processing Technology*, 119, 329-335. doi:[https://doi.org/10.1016/S0924-0136\(01\)00919-0](https://doi.org/10.1016/S0924-0136(01)00919-0)
- Hassan, A. M., Qasim, T., & Ghaithan, A. (2012). Effect of pin profile on friction stir welded aluminum matrix composites. *Materials and Manufacturing Processes*, 27(12), 1397-1401. doi:<https://doi.org/10.1080/10426914.2012.663238>
- How, H. C., & Baker, T. N. (1997). Dry sliding wear behaviour of Saffil-reinforced AA6061 composites. *Wear*, 210(1-2), 263-272. doi:[https://doi.org/10.1016/S0043-1648\(97\)00060-4](https://doi.org/10.1016/S0043-1648(97)00060-4)
- Hu, Q., Zhao, H., & Li, F. (2016). Effect of manufacturing processes on microstructure and properties of Al/A356 B4C composites. *Material and Manufacturing Processes*, 31(10), 1292-1300. doi:<https://doi.org/10.1080/10426914.2016.1151049>
- Huang, L., Duan, T., An, Q., Chen, Y., Bai, J., Geng, L., & Lin, S. (2017). Gas tungsten arc welding of network structured titanium matrix composite. *Science and Technology of Welding and Joining*, 23(5), 357-364. doi:<https://doi.org/10.1080/13621718.2017.1391937>
- Huang, X., Liu, C., Lv, X., Liu, G., & Li, F. (2011). Aluminum alloy piston reinforced with SiC fabricated by centrifugal casting. *Journal of Materials Processing Technology*, 211, 1540-1546. doi:<https://doi.org/10.1016/j.jmatprotec.2011.04.006>
- Hull, D., & Clyne, T. (1996). *An Introduction to Composite Materials*. Great Britain: Cambridge University Press. doi:<https://doi.org/10.1017/CBO9781139170130>
- Inegbenebor, A., Bolu, C., Babalola, P., Inegbenebor, A., & Fayomi, O. (2015). Influence of the Grit Size of Silicon Carbide Particles on the Mechanical and Electrical Properties of Stir Casting Aluminum Matrix Composite Material. *Silicon*, 8, 573-578. doi:<https://doi.org/10.1007/s12633-015-9305-8>
- Jamshidijam, M., Fakhrabadi, A. A., Masoudpanah, S. M., Hasani, G. H., & Mangalaraja, R. (2013). Wear Behavior of Multiwalled Carbon Nanotube/AZ31 Composite Obtained

by Friction Stir Processing. *Tribology Transactions*, 56(3), 827-832.  
doi:<https://doi.org/10.1080/10402004.2013.804969>

Jani, S., Kumar, A. S., Khan, M. A., & Kumar, M. U. (2016). Machinability of hybrid natural fiber composite with and without filler as reinforcement. *Material and Manufacturing Processes*, 31, 1393-1399. doi:<https://doi.org/10.1080/10426914.2015.1117633>

Jayabalakrishnan, D., & Balasubramanian, M. (2018). Eccentric-Weave Friction Stir Welding Between Cu and AA 6061-T6 with Reinforced Graphene Nanoparticles. *Material and Manufacturing Processes*, 1-10. doi:<https://doi.org/10.1080/10426914.2017.1339323>

John, J., Shanmuganathan, S. P., Kiran, M. B., Senthil Kumar, V. S., & Krishnamurthy, R. (2019). Investigation of friction stir processing effect on AA 2014 – T6. *Material and Manufacturing Processes*, 34(2), 159-176.  
doi:<https://doi.org/10.1080/10426914.2018.1532577>

Juang, S. H., Fan, L. J., & Yang, H. P. (2015). Influence of preheating temperatures and adding rates on distributions of fly ash in aluminum matrix composites prepared by stir casting. *International Journal of Precision Engineering and Manufacturing*, 16(7), 1321-1327. doi:<https://doi.org/10.1007/s12541-015-0173-3>

Kaczmar, J., Pietrzak, K., & Wlosinski, W. (2000). The production and application of metal matrix composite materials. *Journal of Materials Processing Technology*, 106(1), 58-67. doi:[https://doi.org/10.1016/S0924-0136\(00\)00639-7](https://doi.org/10.1016/S0924-0136(00)00639-7)

Kalaiselvan, K., & Murugan, N. (2012). Optimizations of friction stir welding process parameter for the welding of Al-B4C composite plates using generalized reduced gradient method. *Procedia Engineering*, 38, 49-55. doi:[10.1016/j.proeng.2012.06.008](https://doi.org/10.1016/j.proeng.2012.06.008)

Kalaiselvan, K., & Murugan, N. (2013). Role of friction stir welding parameters on tensile strength of AA6061/B4C composite joints. *Transactions of Nonferrous Metals Society of China*, 23(2), 616-624. doi:[10.1016/S1003-6326\(13\)62507-8](https://doi.org/10.1016/S1003-6326(13)62507-8)

Kalaiselvan, K., Dinaharan, I., & Murugan, N. (2014). Characterization of friction stir welded boron carbide particulate reinforced AA6061 aluminum alloy stir cast composite. *Materials and Design*, 55, 176-182. doi:[10.1016/J.MATDES.2013.09.067](https://doi.org/10.1016/J.MATDES.2013.09.067)

Khademian, M., Alizadeh, A., & Abdollahi, A. (2016). Fabrication and Characterization of Hot Rolled and Hot Extruded Boron Carbide (B4C) Reinforced A356 Aluminum Alloy Matrix Composites Produced by Stir Casting Method. *Transactions of the Indian Institute of Metals*, 70(6), 1635-1646. doi:[10.1007/s12666-016-0962-0](https://doi.org/10.1007/s12666-016-0962-0)

Khodabakhshi, F., Simchi, A., Kokabi, A. H., Gerlich, A. P., & Nosko, M. (2015). Effects of stored strain energy on restoration mechanisms and texture components in an

aluminum–magnesium alloy prepared by friction stir processing. *Material Science and Engineering A*, 642, 204-214. doi:10.1016/j.msea.2015.07.001

- Kim, C. S., Sohn, I., Nezafati, M., Ferguson, J. B., Schultz, B. F., Bajestani-Gohari, Z., . . . Cho, K. (2013). Prediction models for the yield strength of particle-reinforced unimodal pure magnesium (Mg) metal matrix nanocomposites (MMNCs). *Journal of Materials Science*, 48(12), 4191-4204. doi:10.1007/s10853-013-7232-x
- Kim, H. S. (2000). On the rule of mixtures for the hardness of particle reinforced composites. *Materials Science and Engineering A*, 289, 30-33. doi:[https://doi.org/10.1016/S0921-5093\(00\)00909-6](https://doi.org/10.1016/S0921-5093(00)00909-6)
- Kumar, A., Mahapatra, M. M., Jha, P. K., Mandal, N. R., & Devuri, V. (2014). Influence of tool geometries and process variables on friction stir butt welding of Al-4.5%Cu/TiC In-Situ metal matrix composites. *Materials and Design*, 59, 406-414. doi:10.1016/j.matdes.2014.02.063
- Kumar, A., Nayak, C. V., Herbert, M. A., & Rao, S. S. (2014). Microstructure and hardness of friction stir welded aluminium-copper matrix-based composite reinforced with 10 wt-% SiCp. *Material Research Innovations*, 18, 56-84. doi:<https://doi.org/10.1179/1432891714Z.0000000001016>
- Kumar, B. A., & Murugan, N. (2014). Optimization of friction stir welding process parameters to maximize tensile strength of stir cast AA6061-T6/AlNp composite. *Materials and Design*, 57, 383-393. doi:10.1016/j.matdes.2013.12.065
- Kumaran, S. T., Uthayakumar, M., Slota, A., Aravindan, S., & Zajac, J. (2016). Machining Behavior of AA6351-SiC-B4C Hybrid Composites Fabricated by Stir Casting Method. *Particulate Science and Technology*, 34(5), 586-592. doi:<https://doi.org/10.1080/02726351.2015.1093050>
- Kunze, J. M., & Bampton, C. C. (2001). Challenges to developing and producing MMCs for space application. *The Journal of Minerals, Metals and Material Society*, 53(4), 22-25. doi:<https://doi.org/10.1007/s11837-001-0141-5>
- Kurt, H. L. (2016). Influence of Hybrid Ratio and Friction Stir Processing Parameters on Ultimate Tensile Strength of 5083 Aluminum Matrix Hybrid Composites. *Composites Part B: Engineering*, 93, 26-34. doi:<https://doi.org/10.1016/j.compositesb.2016.02.056>
- Lee, C. J., Huang, J. C., & Hsieh, P. J. (2006). Mg based nano-composites fabricated by friction stir processing. *Scripta Material*, 54(7), 1415-1420. doi:10.1016/j.scriptamat.2005.11.056

- Lee, W. B., Kim, M. K., Yoon, J. I., Kim, Y. J., & Yoen, Y. M. (2006). Microstructures and wear property of friction stir welded AZ91 Mg/SiC particle reinforced composite. *Composites Science and Technology*, 66, 1513-1520. doi:10.1016/j.compscitech.2005.11.023
- Li, Q., Qiu, F., Dong, B. X., Geng, R., Lv, M., Zhao, Q. L., & Jiang, Q. C. (2018). Fabrication, microstructure refinement and strengthening mechanisms of nanosized SiCP/Al composites assisted ultrasonic vibration. *Materials Science & Engineering A*, 735, 310-317. doi:10.1016/j.msea.2018.08.060
- Liu, H., Hu, Y., Zhao, Y., & Fujii, H. (2015). Microstructure and mechanical properties of friction stir welded AC4A + 30 vol.% SiCp composite. *Material and Design*, 65, 395-400. doi:10.1016/j.matdes.2014.09.014
- Liu, J., Khan, U., Coleman, J., Fernandez, B., Rodriguez, P., Naher, S., & Brabazon, D. (2016). Graphene Oxide and Graphene Nanosheet Reinforced Aluminium Matrix Composites: Powder Synthesis and Prepared Composite Characteristics. *Material and Design*, 94, 87-94. doi:<https://doi.org/10.1016/j.matdes.2016.01.031>
- Liu, L., Liang, G., Jie, Z., & Miao, Y. (2003). Study of the net shape diffusion welding mechanism of aluminum matrix composite SiCw/6061Al. *Composite Interfaces*, 10(6), 505-513. doi:10.1163/156855403322667241
- Lloyd, D. J. (1994). Particle reinforced aluminium and magnesium matrix composites. *International Materials Reviews*, 39(1), 1-23. doi:<https://doi.org/10.1179/imr.1994.39.1.1>
- Ma, Z. Y. (2008). Friction Stir Processing Technology: A Review. *Metallurgical and Materials Transaction A*, 39(3), 642-658. doi:<https://doi.org/10.1007/s11661-007-9459-0>
- Mahmoud, E. R., Takahashi, M., Shibayanagi, T., & Ikeuchi, K. (2010). Wear characteristic of surface-hybrid - MMCs layer fabricated on aluminum plate by friction stir processing. *Wear*, 268, 1111-1121. doi:10.1016/J.WEAR.2010.01.005
- Mahoney, M. W., Rhodes, C. G., Flintoff, J. G., Spurling, R. A., & Bingel, W. H. (1998). Properties of Friction-Stir-Welded 7075 T651 Aluminum. *Metallurgical and Materials Transaction A*, 29(7), 1955-1964. doi:<https://doi.org/10.1007/s11661-998-0021-5>
- Mao, J. W., Lu, W. J., Wang, L. Q., Qin, J. N., & Zhang, D. (2014). Microstructures and mechanical properties in laser beam welds of titanium matrix composites. *Science and Technology of Welding and Joining*, 19(2), 142-149.

doi:<https://doi.org/10.1179/1362171813Y.0000000176>

Mao, J. W., Wang, M. M., Wang, L. Q., Xue, X. B., Lu, W. J., Zhang, D., . . . Zhu, X. X. (2012). Weld zone characteristic and mechanical performance of in situ titanium matrix composites using gas tungsten arc welding (GTAW). *Science and Technology of Welding and Joining*, 17(8), 630-635.

doi:<https://doi.org/10.1179/1362171812Y.0000000054>

Marzoli, L. M., Strombeck, A. V., Dos Santos, J. F., Gambaro, C., & Volpone, L. M. (2006). Friction stir welding of an AA6061/Al<sub>2</sub>O<sub>3</sub>/20p reinforced alloy. *Composite Science and Technology*, 66(2), 363-371.

doi:<https://doi.org/10.1016/j.compscitech.2005.04.048>

Mathon, M. H., Klosek, V., Carlan, Y., & Forest, L. (2009). Study of PM2000 microstructure evolution following FSW process. *Journal of Nuclear Materials*, 386(388), 475-478.

doi:[10.1016/j.jnucmat.2008.12.163](https://doi.org/10.1016/j.jnucmat.2008.12.163)

Meilinger, A., & Torok, I. (2013). The importance of friction stir welding tool. *Journal of Production Processes and Systems*, 6(1), 25-34.

Mertens, A., Simar, A., Adrien, J., Maire, E., Montrieu, H. M., Delannay, F., & Beckers, J. L. (2015). Influence of fiber distribution and grain size on the mechanical behaviour of friction stir processed Mg-C composites. *Materials Characterization*, 107, 125-133. doi:[10.1016/j.matchar.2015.07.010](https://doi.org/10.1016/j.matchar.2015.07.010)

Minak, G., Ceschini, L., Boromei, I., & Ponte, M. (2010). Fatigue properties of friction stir welded particulate reinforced aluminium matrix composites. *International Journal of Fatigue*, 32, 218-226. doi:<https://doi.org/10.1016/j.ijfatigue.2009.02.018>

Mishra, R. S., & Ma, Z. Y. (2005). Friction stir welding and processing. *Materials Science and Engineering R: Reports*, 50(1-2), 1-78.

doi:<https://doi.org/10.1016/j.mser.2005.07.001>

Mishra, R. S., Ma, Z. Y., & Charit, I. (2003). Friction stir processing: a novel technique for fabrication of surface composite. *Material Science and Engineering*, 314(A), 307-310. doi:[https://doi.org/10.1016/S0921-5093\(02\)00199-5](https://doi.org/10.1016/S0921-5093(02)00199-5)

Mishra, R. S., Mahoney, M. W., McFadden, S. X., Mara, N. A., & Mukherjee, A. K. (2000). High strain rate superplasticity in a friction stir processed 7075 Al alloy. *Scripta Materialia*, 42(2), 163-168. doi:[https://doi.org/10.1016/S1359-6462\(99\)00329-2](https://doi.org/10.1016/S1359-6462(99)00329-2)

Modi, O. P. (2001). Tow-Body Abrasion of a Cast Al-Cu (2014Al) Alloy-Al<sub>2</sub>O<sub>3</sub> Particle Nanocomposite: Influence of Heat Treatment and Abrasion Test Parameters. *Wear*, 248, 100-111. doi:[10.1007/BF03338093](https://doi.org/10.1007/BF03338093)

- Mohamadreza, N., Abbas, S. M., & Sipro, Y. (2011). Taguchi optimization of process parameters in friction stir welding of 6061 aluminum alloy: A review and case study. *Scientific Research*, 3(2), 144-155. doi:10.4236/eng.2011.32017
- Mollaei, M., Azadi, M., & Tavakoli, H. (2018). A parametric study on mechanical properties of aluminum-silicon/SiO<sub>2</sub> nano-composites by a solid-liquid phase processing. *Applied Physics A*, 124, 504-518. doi:<https://doi.org/10.1007/s00339-018-1929-2>
- Mondal, M., Das, H., Hong, S.-T., Jeong, B.-S., & Han, H. N. (2019). Local enhancement of the material properties of aluminium sheets by a combination of additive manufacturing and friction stir processing. *CIRP Annals*, 68(1), 289–292. doi:<https://doi.org/10.1016/j.cirp.2019.04.109>
- Mortensen, A., & Jin, I. (1992). Solidification processing of metal matrix composites. *International Materials Reviews*, 37(1), 101-128. doi:<https://doi.org/10.1179/imr.1992.37.1.101>
- Moses, J. J., & Sekhar, S. J. (2016). Investigation on the Tensile Strength and Microhardness of AA6061/TiC Composites by Stir Casting. *Transaction of Indian Institute of Metals*, 70(4), 1-12. doi:10.1007/s12666-016-0891-y
- Murugan, N., & Kumar, A. B. (2013). Prediction of tensile strength of friction stir welded stir cast AA6061 T6/AlNp composite. *Materials and Design*, 51, 998-1007. doi:<https://doi.org/10.1016/j.matdes.2013.05.012>
- Nagaral, M., Hiremath, V., Auradi, V., & Kori, S. A. (2018). Influence of Two-Stage Stir Casting Process on Mechanical Characterization and Wear Behavior of AA2014-ZrO<sub>2</sub> Nano-composites. *Transactions of the Indian Institute of Metals*, 71(11), 2845-2850. doi:<https://doi.org/10.1007/s12666-018-1441-6>
- Naher, S., Brabazon, D., & Looney, L. (2003). Simulation of the Stir Casting Process. *Journal of Material Processing and Technology*, 143, 567-571. doi:<https://doi.org/10.1016/j.protcy.2016.05.048>
- Nami, H., Adgi, H., Sharifitabar, M., & Shamabadi, H. (2011). Microstructure and mechanical properties of friction stir welded Al/Mg<sub>2</sub>Si metal matrix cast composite. *Materials and Design*, 32, 976-983. doi:<https://doi.org/10.1016/j.matdes.2010.07.008>
- Narimani, M., Lotfi, B., & Sadeghian, Z. (2016). Evaluation of the microstructure and wear behaviour of AA6063-B4C/TiB<sub>2</sub> mono and hybrid composite layers produced by friction stir processing. *Surface & Coatings Technology*, 285, 1-10. doi:10.1016/j.surfcoat.2015.11.015
- Ni, D. R., Chen, D. L., Wang, D., Xiao, B. L., & Ma, Z. Y. (2013). Influence of

microstructural evolution on tensile properties of friction stir welded joint of rolled SiCp/AA2009-T351 sheet. *Material and Design*, 51, 199-205.  
doi:<https://doi.org/10.1016/j.matdes.2013.04.027>

Ni, D. R., Chen, D. L., Xiao, B. L., Wang, D., & Ma, Z. Y. (2013). Residual stresses and high cycle fatigue properties of friction stir welded SiCp/AA2009 composites. *International Journal of Fatigue*, 55, 64-73.  
doi:<https://doi.org/10.1016/j.ijfatigue.2013.05.010>

Ni, D. R., Chen, D. L., Xiao, B. L., Wang, D., & Ma, Z. Y. (2014). Tensile properties and strain-hardening behaviour of friction stir welded SiCp/AA2009 composite joints. *Material Science and Engineering, A*(608), 1-10. doi:10.1016/j.msea.2014.04.060

Niua, J., Pan, L., Wang, M., Fu, C., & Meng, X. (2006). Research on laser welding of aluminum matrix composite SiCw/6061. *Vacuum*, 80, 1396-1399.  
doi:10.1016/j.vacuum.2006.01.023

Ourdjini, A., Chew, K. C., & Khoo, B. T. (2001). Settling of silicon carbide particles in cast metal matrix composites. *Journal of Materials Processing Technology*, 116, 72-76.  
doi:[https://doi.org/10.1016/S0924-0136\(01\)00843-3](https://doi.org/10.1016/S0924-0136(01)00843-3)

Pantelis, D. I., Karakizis, P. N., Daniolos, N. M., Charitidis, C. A., Koumoulos, E. P., & Dragatogiannis, D. A. (2015). Microstructural Study and Mechanical Properties of Dissimilar Friction Stir Welded AA5083-H111 and AA6082-T6 Reinforced with SiC Nanoparticles. *Materials and Manufacturing Processes*, 31(3), 264-274.  
doi:<https://doi.org/10.1080/10426914.2015.1019095>

Parikh, V. K., Badgujar, A. D., & Ghetiya, N. D. (2019). Joining of metal matrix composites using friction stir welding: a review. *Material and Manufacturing Processes*, 34(2), 123-146. doi:<https://doi.org/10.1080/10426914.2018.1532094>

Patel, K., Pandey, P. M., & Rao, P. V. (2011). Study on machinability of Al<sub>2</sub>O<sub>3</sub> ceramic composite in EDM using response surface methodology. *Journal of Engineering Materials and Technology*, 133(2), 021004. doi:<https://doi.org/10.1115/1.4003100>

Patel, V. V., Badheka, V., & Kumar, A. (2016). Friction stir processing as a novel technique to achieve superplasticity in aluminum alloys: process variables, variants, and applications. *Metallography, Microstructure, and Analysis*, 5(4), 278-293.  
doi:<https://doi.org/10.1007/s13632-016-0285-x>

Pech-Canul, M. K. (2000). Optimum parameters for wetting silicon carbide by aluminum alloys. *Metallurgical and Materials Transactions*, 31(A), 565-573.  
doi:<https://doi.org/10.1007/s11661-000-0291-z>

- Peng, K., Cui, H. C., Lu, F. G., Wu, X. M., Tang, X. H., Yao, S., & Lou, S. N. (2011). Mechanical properties and wear resistance of aluminum composites welded by electron beam. *Transactions of Nonferrous Metals Society of China*, 21, 1925-1931. doi:[https://doi.org/10.1016/S1003-6326\(11\)60951-5](https://doi.org/10.1016/S1003-6326(11)60951-5)
- Periyasamy, P., Mohan, B., & Balasubramanian, V. (2012). Effect of heat input on mechanical and metallurgical properties of friction stir welded AA6061-10% SiCp MMCs. *Journal of Material Engineering and Performance*, 21(11), 2417- 2428. doi:[10.1007/s11665-012-0176-5](https://doi.org/10.1007/s11665-012-0176-5)
- Periyasamy, P., Mohan, B., Balasubramanian, V., Rajakumar, S., & Venugopal, S. (2013). Multi-objective optimization of friction stir welding parameters using desirability approach to join Al/SiCp metal matrix composites. *Transactions of Nonferrous Metals Society of China*, 23(3), 942-955. doi:[https://doi.org/10.1016/S1003-6326\(13\)62551-0](https://doi.org/10.1016/S1003-6326(13)62551-0)
- Poovazhagan, L. K. (2013). Characterization of Hybrid Silicon Carbide and Boron Carbide Nanoparticles-Reinforced Aluminum Alloy Composites. *Procedia Engineering*, 64, 681-689. doi:<https://doi.org/10.1016/j.proeng.2013.09.143>
- Prabu, S. B., Karunamoorthy, L., Kathiresan, S., & Mohan, B. (2006). Influence of stirring speed and stirring time on distribution of particles in cast metal matrix composites. *Journal of Material Processing Technology*, 171, 268-273. doi:[10.1016/j.jmatprotec.2005.06.071](https://doi.org/10.1016/j.jmatprotec.2005.06.071)
- Rahsepar, M., & Jarahimoghadam, H. (2016). The Influence of Multipass Friction Stir Processing on the Corrosion Behavior and Mechanical Properties of Zircon-Reinforced Al Metal Matrix Composites. *Material Science and Engineering A*, 671, 214-220. doi:<https://doi.org/10.1016/j.msea.2016.05.056>
- Raj, R., & Thakur, D. G. (2016). Qualitative and quantitative assessment of microstructure in Al-B4C metal matrix composite processed by modified stir casting technique. *Archives of Civil and Mechanical Engineering*, 16(4), 949-960. doi:<https://doi.org/10.1016/j.acme.2016.07.004>
- Rana, H., & Badheka, V. (2018). Influence of friction stir processing conditions on the manufacturing of Al-Mg-Zn-Cu alloy/boron carbide surface composite. *Journal of Materials Processing Technology*, 255, 795-807. doi:[10.1016/j.jmatprotec.2018.01.020](https://doi.org/10.1016/j.jmatprotec.2018.01.020)
- Rana, H., & Badheka, V. (2019). Elucidation of the role of rotation speed and stirring direction on AA 7075-B4C surface composites formulated by friction stir processing.

- Proceeding of the Institution of Mechanical Engineers, Part L: Journal of Materials: Design and Application*, 233(5), 1-18. doi:<https://doi.org/10.1177/1464420717736548>
- Rao, R. N., & Das, S. (2011). Effect of sliding distance on the wear and friction behavior of as cast and heat-treated Al–SiCp composites. *Materials & Design*, 32(5), 3051-3058. doi:[10.1016/j.matdes.2011.01.033](https://doi.org/10.1016/j.matdes.2011.01.033)
- Rathee, S., Maheshwari, S., Siddiquee, A. N., & Srivastava, M. (2017). Investigating Effects of Groove Dimensions on Microstructure and Mechanical Properties of AA6063/SiC Surface Composites Produced by Friction Stir Processing. *Transactions of the Indian Institute of Metals*, 70(3), 809-816. doi:<https://doi.org/10.1007/s12666-017-1060-7>
- Ravi, B., Naik, B. B., & Prakash, J. U. (2015). Characterization of Aluminium Matrix Composites (AA6061/B4C) Fabricated by Stir Casting Technique. *Materials Today: Proceedings*, 2(4-5), 2984 - 2990. doi:<https://doi.org/10.1016/j.matpr.2015.07.282>
- Reddy, A. S., Bai, B. N., Murthy, K. S., & Biswas, S. K. (1994). Wear and seizure of binary Al/Si alloys. *Wear*, 171(1-2), 115-127. doi:[https://doi.org/10.1016/0043-1648\(94\)90354-9](https://doi.org/10.1016/0043-1648(94)90354-9)
- Rino, J. J., Chandramohan, D., & Sucitharan, K. (2012). An overview on development of aluminium metal matrix composites with hybrid reinforcement. *International Journal of Scientific Research*, 1(3), 196-203. doi:ISSN: 2319-7064
- Rosenberger, M. R., Schvezov, C. E., & Forlerer, E. (2005). Wear of different aluminum matrix composites under conditions. *Wear*, 259(1), 590-601. doi:[10.1016/j.wear.2005.02.003](https://doi.org/10.1016/j.wear.2005.02.003)
- Sajjadi, S., Ezatpour, H., & Beygi, H. (2011). Microstructure and Mechanical Properties of Al-Al<sub>2</sub>O<sub>3</sub> Micro and Nano Composites Fabricated by Stir Casting. *Material Science and Engineering A*, 528(29-30), 8765-8771. doi:<https://doi.org/10.1016/j.msea.2011.08.052>
- Sankhla, A., & Patel, K. M. (2021). Metal Matrix Composites Fabricated by Stir Casting Process—A Review. *Advances in Materials and Processing Technologies*. doi:<https://doi.org/10.1080/2374068X.2020.1855404>
- Sathiskumar, R. M. (2013). Role of friction stir processing parameters on microstructure and microhardness of boron carbide particulate reinforced copper surface composites. *Sadhana*, 38(5), 1-18. doi:[10.1007/s12046-013-0184-7](https://doi.org/10.1007/s12046-013-0184-7)
- Savaskan, T., & Bican, O. (2010). Dry Sliding Friction and Wear Properties of Al–25Zn–3Cu–(0–5)Si Alloys in the As-Cast and Heat-Treated Conditions. *Tribology Letters*, 40, 327-336. doi:<https://doi.org/10.1007/s11249-010-9667-4>

- Sekar, K., Allesu, K., & Joseph, M. (2013). Design, Construction and Performance Evaluation of Multiple Casting Machine. *Nigerian Journal of Technology*, 32(3), 498-506. doi:ISSN: 0331-8443
- Sekar, K., Allesu, K., & Joseph, M. A. (2015). Mechanical and Wear Properties of Al-Al<sub>2</sub>O<sub>3</sub> Metal Matrix Composites Fabricated by the Combined Effect of Stir and Squeeze Casting Method. *Transactions of the Indian Institute of Metals*, 68(2), 115-121. doi:10.1007/s12666-015-0520-1
- Shabani, M. O., Baghani, A., Khorram, A., & Heydari, F. (2020). Evaluation of fracture mechanisms in Al-Si metal matrix nanocomposites produced by three methods of gravity sand casting, squeeze casting and compo casting in semi-solid state. *Silicon*, 12, 2977-2987. doi:<https://doi.org/10.1007/s12633-020-00390-9>
- Shabani, M. O., Rahimipour, M. R., Tofigh, A. A., & Davami, P. (2015). Refined microstructure of compo cast nanocomposites: the performance of combined neuro-computing, fuzzy logic and particle swarm techniques. *Neural Computing and Application*, 26(4), 899–909. doi:10.1007/s00521-014-1724-8
- Shah, C., Goyal, B., & Patel, V. (2015). Optimization of FSW process parameters for AlSiCp PRMMC using ANOVA. *Materials Today: Proceedings*, 2, 2504 - 2511. doi:10.1016/j.matpr.2015.07.195
- Shaik, D., Sudhakar, I., Bharat, G. C., Varshini, V., & Vikas, S. (2020). Tribological behavior of friction stir processed AA6061 aluminium alloy. *Materials Today: Proceedings*, 44(1), 860-864. doi:<https://doi.org/10.1016/j.matpr.2020.10.788>
- Shettigar, K., Salian, G., Herbert, M., & Rao, S. (2013). Microstructural Characterization and Hardness Evaluation of Friction Stir Welded Composite AA6061-4.5Cu-5SiC (Wt.%). *Defence Science Journal*, 63(4), 429-434. doi:<https://doi.org/10.14429/dsj.63.4869>
- Shorowordi, K., Laoui, T., Haseeb, A., Celis, J. P., & Froyen, L. (2003). Microstructure and interface characteristics of B4C, SiC and Al<sub>2</sub>O<sub>3</sub> reinforced Al matrix composites: A comparative study. *Journal of Materials Processing Technology*, 142(3), 738-743. doi:[https://doi.org/10.1016/S0924-0136\(03\)00815-X](https://doi.org/10.1016/S0924-0136(03)00815-X)
- Sijo, M. T., & Jayadevan, K. R. (2016). Analysis of stir cast aluminium silicon carbide metal matrix composite: A comprehensive review. *Procedia Technology*, 24, 379 - 385. doi:<https://doi.org/10.1016/j.protcy.2016.05.052>
- Simar, A., & Avettand-Fenoel, M. N. (2016). State of the art about dissimilar metal friction stir welding. *Science and Technology of Welding and Joining*, 22(5), 1-15.

doi:<https://doi.org/10.1080/13621718.2016.1251712>

- Singh, A., & Bala, N. (2017). Fabrication and Tribological Behavior of Stir Cast Mg/B4C Metal Matrix Composites. *Metallurgical and Materials Transaction A*, 48(10), 5031-5045. doi:10.1007/s11661-017-4203-x
- Singh, G., & Goyal, S. (2016). Microstructure and mechanical behavior of AA6082-T6/SiC/B4C-based aluminum hybrid composites. *Particulate Science and Technology*, 36(2), 154-161. doi:<https://doi.org/10.1080/02726351.2016.1227410>
- Singh, J., & Chauhan, A. (2016). Overview of wear performance of aluminium matrix composites reinforced with ceramic materials under the influence of controllable variables. *Ceramics International*, 42(1(A)), 56-81. doi:10.1016/j.ceramint.2015.08.150
- Soltani, S., Khosroshahi, R. A., Mousavian, R. T., Jiang, Z. Y., Boostani, A. F., & Brabazon, D. (2017). Stir casting process for manufacture of Al-SiC composites. *Rare Metals*, 36(7), 581-590. doi:<https://doi.org/10.1007/s12598-015-0565-7>
- Sozhamannan, G. G., Prabu, S. B., & Venkatagalapathy, V. S. (2012). Effect of Processing Parameters on Metal Matrix Composites: Stir Casting Process. *Journal of Surfaced Engineered Materials and Advanced Technology*, 2(1), 11-15. doi:10.4236/jsemat.2012.21002
- Srivatsan, T. (1995). A Review of: Fundamentals of Composites Manufacturing: Materials, Methods and Applications. *Material and Manufacturing Processes*, 10(5), 1121-1122. doi:<https://doi.org/10.1080/10426919508935097>
- Storjohann, D., Barabash, O. M., Babu, S. S., David, S. A., Sklad, P. S., & Bloom, E. E. (2005). Fusion and Friction Stir Welding of Aluminum-Metal-Matrix Composites. *Metallurgical and Materials Transactions A*, 36a, 3237-3247. doi:<https://doi.org/10.1007/s11661-005-0093-4>
- Sunil, B. R., Reddy, G. P., Patle, H., & Dumpala, R. (2016). Magnesium based surface metal matrix composites by friction stir processing. *Journal of Magnesium and Alloys*, 4(1), 52-61. doi:<https://doi.org/10.1016/j.jma.2016.02.001>
- Surappa, M. (1997). Microstructure Evolution During Solidification of DRMMCs (Discontinuously Reinforced Metal Matrix Composites): State of Art. *Journal of Material Processing Technology*, 63(1-3), 325-333. doi:[https://doi.org/10.1016/S0924-0136\(96\)02643-X](https://doi.org/10.1016/S0924-0136(96)02643-X)
- Suresh, S., Mortensen, A., & Needleman, A. (1993). *Fundamentals of Metal-Matrix Composites*. Oxford: Butterworth-Heinemann. doi:ISBN 978-0-08-052371-2

- Suthar, J., & Patel, K. M. (2018). Processing issues, machining, and applications of aluminum metal matrix composites. *Materials and Manufacturing Processes*, 33(5), 499-527. doi:<https://doi.org/10.1080/10426914.2017.1401713>
- Sutton, M. A., Yang, B., Reynolds, A. P., & Taylor, R. (2002). Microstructural studies of friction stir welds in 2024-T3 aluminum. *Material Science and Engineering A*, 323, 160–166. doi:[10.1016/S0921-5093\(01\)01358-2](https://doi.org/10.1016/S0921-5093(01)01358-2)
- Taha, M. A. (2001). Industrialization of Cast Aluminum Matrix Composites (AMCCs). *Material and Manufacturing Processes*, 16(5), 619-641. doi:[10.1081/AMP-100108625](https://doi.org/10.1081/AMP-100108625)
- Thankachan, T., Prakash, K. S., & Kavimani, V. (2018a). Investigation on the effect of friction stir processing on Cu-BN surface composite. *Material and Manufacturing Processes*, 33(3), 299-307. doi:<https://doi.org/10.1080/10426914.2017.1291952>
- Thankachan, T., Prakash, K. S., & Kavimani, V. (2018b). Effect of Friction Stir Processing and Hybrid Reinforcement on copper. *Material and Manufacturing Processes*, 33(15), 1681-1692. doi:<https://doi.org/10.1080/10426914.2018.1453149>
- Thomas, W., Nicholas, E., Needham, J., Murch, M., Temple-Smith, P., & Dawes, C. (1991, 12 06). Patent No. GB9125978A. USA.
- Tofigh, A. A., Rahimipour, M. R., Shabani, M. O., & Davami, P. (2015). Application of the combined neuro-computing, fuzzy logic and swarm intelligence for optimization of compocast nanocomposites. *Journal of Composite Material*, 49(13), 1653–1663. doi:<https://doi.org/10.1177/0021998314538871>
- Uematsu, Y., & Tokaji, K. (2010). Fatigue behaviour of friction stir processed cast aluminium and magnesium alloys. *Material Science and Forum*, 638–642, 3727–3732. doi:<https://doi.org/10.4028/www.scientific.net/MSF.638-642.3727>
- Uzun, H. (2007). Friction stir welding of SiC particulate reinforced AA2124 aluminium alloy matrix composite. *Materials and Design*, 28(5), 1440-1446. doi:[10.1016/j.matdes.2006.03.023](https://doi.org/10.1016/j.matdes.2006.03.023)
- Verdian, M. (2010). Synthesis of TiAl<sub>3</sub>-Al<sub>2</sub>O<sub>3</sub> composite particles by chemical reaction in molten salts. *Material and Manufacturing Processes*, 25(9), 953-955. doi:[10.1080/10426911003720748](https://doi.org/10.1080/10426911003720748)
- Vijay, S. J., & Murugan, N. (2010). Influence of tool pin profile on the metallurgical and mechanical properties of friction stir welded Al-10 wt.% TiB<sub>2</sub> metal matrix composite. *Materials and Design*, 31(7), 3585-3589. doi:<https://doi.org/10.1016/j.matdes.2010.01.018>

- Wang, A., & Rack, H. J. (1991). Transition wear behavior of SiC-particulate- and SiC-whisker-reinforced 7091 Al metal matrix composites. *Materials Science and Engineering: A*, 147(2), 211-224. doi:10.1016/0921-5093(91)90848-H
- Wang, D., Wang, Q. Z., Xiao, B. L., & Ma, Z. Y. (2014). Achieving friction stir welded SiCp/Al-Cu-Mg composite joint of nearly equal strength to base material at high welding speed. *Materials Science & Engineering A*, 589, 271-274. doi:10.1016/j.msea.2013.09.096
- Wang, D., Xiao, B. L., Wang, Q. Z., & Ma, Z. Y. (2013). Friction stir welding of SiCp/2009Al composite plate. *Materials and Design*, 47, 243-247. doi:<https://doi.org/10.1016/j.matdes.2012.11.052>
- Wang, D., Xiao, B. L., Wang, Q. Z., & Ma, Z. Y. (2014). Evolution of the Microstructure and Strength in the nugget zone of friction stir welded SiCp/Al-Cu-Mg Composite. *Journal of Material Science and Technology*, 30(1), 54-60. doi:10.1016/j.jmst.2013.09.018
- Wang, H. M., Chen, Y. L., & Yu, L. G. (2000). In-situ weld-alloying/laser beam welding of SiCp/6061Al MMC. *Material Science and Engineering A*, 293(1-2), 1-6. doi:10.1016/S0921-5093(00)01249-1
- Wang, J., Yuan, W., Mishra, R. S., & Charit, I. (2013). Microstructural evolution and mechanical properties of friction stir welded ODS alloy MA754. *Journal of Nuclear Materials*, 442(1-3), 1-6. doi:<https://doi.org/10.1016/j.jnucmat.2013.08.012>
- Wang, J., Yuan, W., Mishra, R. S., & Charit, I. (2013(a)). Microstructure and mechanical properties of friction stir welded oxide dispersion strengthened alloy. *Journal of Nuclear Material*, 432(1-3), 274-280. doi:<https://doi.org/10.1016/j.jnucmat.2012.08.001>
- Wang, X. J., Hu, X. S., Wu, K., Zheng, M. Y., Zheng, L., & Zhai, Q. J. (2009). The interfacial characteristic of SiCp/AZ91 magnesium matrix composites fabricated by stir casting. *Journal of Materials Science*, 44(11), 2759-2764. doi:10.1007/s10853-009-3360-8
- Wranglen, G. (1970). The Rustless Iron Pillar at Delhi. *Corrosion Science*, 10, 761-770.
- Xiao, B. L., Wang, D., Bi, J., Zhang, Z., & Ma, Z. Y. (2010). Friction stir welding of SiCp/Al composite and 2024 Al alloy. *Materials Science Forum*, 638(642), 1500-1505. doi:<https://doi.org/10.4028/www.scientific.net/MSF.638-642.1500>
- Xuan, Z. Z., Gu, X. Y., Zhong, R., & Sun, D. Q. (2010). Microstructures and mechanical properties of tungsten inert gas arc welded magnesium metal matrix composite

(TiCp/AZ91D). *Material Science and Technology*, 26(12), 1513-1517.  
doi:<https://doi.org/10.1179/026708309X12506933872900>

Xue, P., Xie, G. M., Xiao, B. L., Ma, Z. Y., & Geng, L. (2010). Effect of Heat Input Conditions on Microstructure and Mechanical Properties of Friction-Stir-Welded Pure Copper. *Metallurgical and Materials Transactions A*, 41(8), 2010-2021.  
doi:10.1007/s11661-010-0254-y

Yabuuchi, K., Tsuda, N., Kimura, A., Morisada, Y., Fujii, H., & Serizawa, H. (2014). Effect of tool rotational speed on the mechanical properties and microstructure of friction stir welded ODS steel. *Material Science and Engineering*, 595, 291-296.  
doi:<https://doi.org/10.1016/j.msea.2013.12.022>

Yang, B., Yan, J., Sutton, M. A., & Reynolds, A. P. (2004). Banded microstructure in AA 2024-T351 and AA 2524-T351 aluminum friction stir welds Part I. Metallurgical studies. *Material Science and Engineering A*, 364(1-2), 55-65. doi:10.1016/S0921-5093(03)00532-X

Yigezu, B. S., Jha, P. K., & Mahapatra, M. M. (2013). The key attributes of synthesizing ceramic particulate reinforced Al-based matrix composites through stir casting process: A Review. *Material and Manufacturing Processes*, 28(9), 969-979.  
doi:10.1080/10426914.2012.677909

Yigezu, B. S., Venkateswarlu, D., Mahapatra, M. M., Jha, P. K., & Mandal, N. R. (2014). On friction stir butt welding of Al + 12Si/10 wt%TiC in situ composite. *Materials and Design*, 54, 1019-1027. doi:10.1016/j.matdes.2013.09.034

Yu, L. I., Qiu-lin, L. I., Dong, L. I., Wei, L. I., & U., G.-g. S. (2016). Fabrication and characterization of stir casting AA6061-31%B4C composite. *Transactions of Nonferrous Metals Society of China*, 26(9), 2304-2312.  
doi:[https://doi.org/10.1016/S1003-6326\(16\)64322-4](https://doi.org/10.1016/S1003-6326(16)64322-4)

Zhang, L., Duan, Z., Zhu, H., & Yin, K. (2017). Advances in Synthesizing Copper/Graphene Composite Material. *Material and Manufacturing Processes*, 32(5), 475-479.  
doi:<https://doi.org/10.1080/10426914.2016.1198036>

Zhang, X. P., Quan, G. F., & Wei, W. (1999). Preliminary investigation on joining performance of SiC reinforced aluminium metal matrix composites (Al/SiCpMMC) by vacuum brazing. *Composites:Part A*, 30(6), 823-827. doi:10.1016/S1359-835X(98)00186-9

Zhang, Z., & Chen, D. L. (2008). Contribution of Orowan strengthening effect in particulate-reinforced metal matrix nanocomposites. *Material Science and Engineering: A*, 483-

484, 148-152. doi:<https://doi.org/10.1016/j.msea.2006.10.184>

Zhao, W. W., Yan, J. C., & Fu, Q. J. (2009). Ultrasonic brazing of aluminium matrix composites assisted by operation of melting and squeezing. *Material Science and Technology*, 25(12), 1474-1477. doi:<https://doi.org/10.1179/174328408X378861>

Zhiqiang, S., Di, Z., & Guobin, L. (2005). Evaluation of dry sliding wear behavior of silicon particles reinforced aluminum matrix composites. *Materials & Design*, 26(5), 454-458. doi:<https://doi.org/10.1016/j.matdes.2004.07.026>

Zvolinskii, I. V., Kuchuk-Yatsenko, V. S., Khorunov, V. F., Shvets, V. I., Ivanov, V. A., Fedotov, N. A., . . . Trubkina, E. M. (1995). Special features of braze welding metal matrix composites. *Welding International*, 9(1), 41-43. doi:<https://doi.org/10.1080/09507119509548750>